

ABSTRACT

A revolving-door assembly includes a plurality of radially-extending door sections rotatably mounted about a vertical rotary axis within a passageway for controlling the flow of traffic through said passageway. Each of the radially-extending door sections includes a radially-extending inner panel and at least one radially-extending outer panel. The radially-extending inner panels are mounted for rotation about the vertical rotary axis. Each of the radially-extending outer panels is movable radially outwardly away from, and inwardly towards, the respective radially-extending inner panels to assume an outermost position when the respective radially-extending door section is located perpendicularly to the flow of traffic, and an innermost position when the respective radially-extending door section is located parallel to the flow of traffic. Two embodiments are described wherein there are four door sections, each including one or two outer panels; and two further embodiments are described wherein there are two door sections each including one or two outer panels.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011753 A2

(51) International Patent Classification⁷: E06B

(21) International Application Number:
PCT/IL2003/000613

(22) International Filing Date: 24 July 2003 (24.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/399,410 31 July 2002 (31.07.2002) US

(71) Applicant and

(72) Inventor: ARIAV, Arie [IL/IL]; 122 Kochav Michael, 79
304 Doar Na Hof Ashkelon (IL).

(74) Agent: G. E. EHRLICH (1995) LTD.; 11 Menachem Be-
gin Street, 52 521 Ramat Gan (IL).

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO,
RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: REVOLVING-DOOR ASSEMBLY

(57) **Abstract:** A revolving-door assembly includes a plurality of radially-extending door sections rotatably mounted about a ver-
tical rotary axis within a passageway for controlling the flow of traffic through said passageway. Each of the radially-extending
door sections includes a radially-extending inner panel and at least one radially-extending outer panel. The radially-extending in-
ner panels are mounted for rotation about the vertical rotary axis. Each of the radially-extending outer panels is movable radially
outwardly away from, and inwardly towards, the respective radially-extending inner panels to assume an outermost position when
the respective radially-extending door section is located perpendicularly to the flow of traffic, and an innermost position when the
respective radially-extending door section is located parallel to the flow of traffic. Two embodiments are described wherein there are
four door sections, each including one or two outer panels; and two further embodiments are described wherein there are two door
sections each including one or two outer panels.



WO 2004/011753 A2